



A robust design for increased versatility and maneuverability for maintenance work.

Rated to 46kv, the Altec AT37M features an added material handling package. Also, with the jib and winch fitted, the bucket capacity is not reduced, as with other makes. The AT37M can be easily mounted onto a 10t GVW chassis. This 2-man platform has 180° hydraulic platform rotation with platform tilt, and 272kg platform capacity.

FEATURES

- Insulating; ANSI 92.2 Category C and EN61057
- Altec ISO-Grip® control system (U.S. Patent No. 7,416,053)
- 4-function, single handle upper control dielectrically tested to 40kV AC with no more than 400 microamperes of leakage. (The control handle is green in colour to differentiate it from other non-tested controllers)
- Compensated articulating arm
- Fiberglass lower boom and telescopic inner boom
- Fiberglass single 2-man platform, 24" x 48" x 42"
- Hydraulic boom extension
- Platform access from ground

- Altec ARM jib capacities up to 362.9kg
- Full-pressure, open-centre hydraulic system
- Tool circuit at platform
- Emergency stop valves at all upper and lower control stations
- Secondary stowage system
- Engine start/stop
- Second tool circuit at platform

OPTIONS

- Emergency pump run function on engagement of PTO
- Strong arm jib removal lift and storage system
- Set of spreaderfeet
- Many others on request

